



®

Product Specification

PORTER'S LIMEPROOF UNDERCOAT SEALER

PRODUCT DESCRIPTION:

Porter's Limeproof Undercoat Sealer is an exterior/interior use undercoat primer/sealer that can be applied to bare paintable surfaces as an undercoat sealer, or for use over previously painted surfaces as an undercoat primer prior to the application of any Porter's paint or finish. White in colour. Ultra matt finish.

LOCATION:

Interior or exterior.

ENVIRONMENTAL INFORMATION:

This product contains: 20.85g/L VOC's (Volatile Organic Compounds contribute to atmospheric pollution).

The following descriptors have been adopted by APAS (Australian Paint Approval Scheme):

Very High	>250 g/L
High	100 – 249 g/L
Moderate	50 – 99 g/L
Low	5 – 49 g/L
Very Low	<5 g/L

This product is classified as Low VOC by the Australian Paint Approval Scheme. (Volatile Organic Compounds contribute to atmospheric pollution).

Porter's Paints use only premium grade raw materials and wherever possible we buy from Australian suppliers. Our manufacturing processes are designed for maximum performance with minimum impact on the environment and user health.

SUGGESTED APPLICATIONS:

Can be applied to most suitably prepared interior or exterior surfaces, including masonry and plaster board.

COLOUR:

Porter's Limeproof Undercoat Sealer is supplied white. May be tinted if required.

LIMITATIONS:

Not suitable over new/bare set plaster. Not suitable for use over previously oiled timbers. Do not apply in high humidity, below 10°C or above 30°C.

PREPARATION:

The substrate should be a clean well-held surface free from loose material, dirt, dust, grease, oil, release agents, mould and anything else likely to inhibit adhesion.

Newly completed walls should be left to cure before the application of Porter's Limeproof Undercoat Sealer. Minimum drying/curing times:

Cement render	28 days
Cement "bagged" surface	14 days
Bricks and mortar	56 days

Filled concrete blocks	56 days
Pre-cast and in-situ concrete	56 days

On new unpainted fresh set plaster do not proceed until plaster has thoroughly set and has dried completely. Firstly, apply 1 coat Porter's Mineral Silicate Primer by brush or roller. Touch dry 20 minutes. Allow 2 hours dry time. Then apply by brush, roller or spray 1 coat Porter's Limeproof Undercoat Sealer. Touch dry 2 hours. Allow 6 hours dry time.

RE-COATING LIME WASH OR INTERNO:

Ensure the surface to be undercoated is a clean well-held surface free from loose material, dirt, dust, grease, oil, mould and anything else likely to inhibit adhesion.

Lime washes, particularly on exteriors, can weather and age, creating a powdery surface. Although this powdery residue is normal for lime wash, when intending to apply any further coats, including undercoats and sealers, this powdery residue must be removed, and the surface made stable.

APPLICATION:

Stir thoroughly prior to use. Apply one or two coats by brush, medium nap roller or spray. Touch dry in 1 hour. Allow minimum 6 hours dry time between coats. Allow 6 hours dry time before over-coating.

Spray details (recommended by Wagner):

Tip size: 24thou. Filter: Green

COVERAGE RATES:

Covers approximately 12m² per litre, depending upon porosity, surface texture and wastage rates.

WASH UP:

Water.

PACKAGING:

Porter's Limeproof Undercoat Sealer is available in 1 litre, 4 litre, 10 litre & 15 litre sizes.

STORAGE:

Store in a cool dry area, protected from frost.

PRECAUTIONS:

Keep out of reach of children. Avoid swallowing. Avoid eye contact. Avoid prolonged skin contact. Provide adequate ventilation. If accidental contact occurs, rinse immediately with water.

MANUFACTURER'S/DISTRIBUTOR'S DETAILS:

Porter's Paints

15 Gow St

Padstow NSW 2211

Australia

Phone: (02) 9698-5322

Toll free: 1800 656 664

Fax: (02) 9699-5322

E-mail: enquiries@porters.com.au

Web: www.porterspains.com

Porter's Paints

150 Hutt Park Rd

Gracefield

Lower Hutt 5010

New Zealand

Ph: 0800 672 468