

REVIVE METALLICS



APPLICATION GUIDE

PORTER'S PAINTS

SUITABLE SURFACES & COLOURS

Revive Metallics

Revive Metallics is a range of 8 little gems of 4 glittery golds and 4 pearlescent silvers for decorating frames, furniture and small projects.

Liquid Gold adds a subtle touch of luxury and sophistication to trim, picture frames, pots and furniture. Available in 4 rich hues, Liquid Gold is a water-based decorative metallic gold.

Duchess Satin is a water based pearlescent paint with the rich lustre of satin fabric. Add dimension and texture whilst creating a delicate pearly glitter on frames, trims, architraves or furniture.

Most household marks and stains easily wipe away. For interior use.

Suitable Surfaces:

Suitable for most paintable surfaces, including previously varnished, lacquered or painted furniture. Also suitable for picture frames and trim.

Colours:

There are eight popular colours, factory tinted and ready to go.

PORTER'S PAINTS

TOOLS & SURFACE PREPARTION

Estimate your paint needs:

Revive Metallics cover approximately 8-10 square metres per litre, which means that a 100ml pot will cover approximately 1 square metre. Take into account that two to three coats are required for optimum coverage.

Choose your tools:

Apply by brush. Visible brushstrokes are a characteristic of metallic and pearlescent paints, and it is for this reason that we do not recommend application with a paint roller.

Clean & Prepare:

All pieces should be thoroughly cleaned to remove dust, dirt and grime, and if necessary, degreased.

For best results, prime before painting. Lightly sand the surface and wipe clean, then apply 1 coat of Porter's Prepare & Prime (a multisurfaces primer and stain blocker). Allow to dry for 2 hours before applying the topcoat.

PORTER'S PAINTS

APPLICATION & DRY TIIMES

Application of paint:

First Coat:

Paint a thin coat in the direction of the grain of the wood, using long strokes. Paint from end to end. Avoid short brush strokes, and repeatedly brushing back over the paint as it is drying, as this will cause stop/start marks and brushstroke texture.

Touch dry in 1 hour. Allow a minimum of 4 hours dry time before applying the second coat.

Second Coat:

Inspect your project and gently sand off any drips. Apply a second coat as you did for the first coat, using long strokes and brushing from end to end to avoid start/stop marks.

Touch dry in 1 hour. Allow to dry for 6 hours, or if more than two coats are required, allow 4 hours before recoating.

Note: As visible brushstrokes are a characteristic of metallic and pearlescent paints, application methods will vary end results.



WASH UP & LIMITATIONS

Wash Up:
Water
Limitations:
Do not apply in high humidity, below 10°c or above 30°c.

Help & Advice:

AU: 1800 656 664 NZ: 0800 672 648

Safety Directions

May cause an allergic skin reaction. Keep out of reach of children. Avoid breathing dust, fume, gas, mist, vapours or spray. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves/protective clothing including eye/face protection. SPILLS & LEAKS: Slippery when spilt. Wear protective equipment. For liquids absorb with sand or soil. Collect and seal in properly labelled drums. Refer to local authority for disposal advice. FIRST AID: If poisoning occurs, contact a Doctor or Poisons Information Centre (Phone Australia 131 126; New Zealand 0800 764 766). If medical advice is needed, have product container or label at hand. SWALLOWED: If swallowed, do NOT induce vomiting. Give a glass of water. Seek medical advice. EYE: If in eyes, hold eyes open, rinse cautiously with water for at least 15 minutes and see a doctor. SKIN: If skin contact occurs, remove contaminated clothing and wash skin thoroughly. If irritation occurs seek medical advice. INHALED: Remove from contaminated area. DO NOT REUSE CONTAINER UNLESS THOROUGHLY DECONTAMINATED. EMERGENCY INFORMATION (ALL HOURS): AUST-1800 220 770 NZ-0800 220 770